

TECHNICAL DATASHEET

PUR T54 D FR

Material	Flame resistant compound based on thermoplastic polyether based polyurethane – TPU	
Product code	PU10	
Product type	- Tape	
Application	Cable markers	
Characteristics	Specially developed polyether-polyurethane halogen-free compound for cable markers, which offers excellent flexibility, flame retardancy and coloration.	
	Chemical:	Limited Please contact us for additional information
	UV- & weather:	Poor unless special additives is added
	Working temperature:	-40°C to +80°C
	Flame resistance:	V0 at 3,0 mm (UL 94) V2 at 0,75 mm (UL 94)
	Surface hardness:	Shore D 58
Standard/Norms	-	
Compliance	<ul style="list-style-type: none"> - EC Regulation 1907/2006 (REACH) - Directive 2011/65/EU (ROHS) - Do not contain dual use additives 	
Dimension	Thickness:	0,5 to 1,0 mm
	Width:	40 to 110 mm
Color	Standard:	White, yellow, black, red, orange and blue
	Specialties:	Special colors at an additional charge
Packaging	Free coils of 100 m placed in carton boxes	
Origin	Products are “Made in Denmark” and raw material for the products originates from the EU	
Documentation	Specific documentation is available for: <ul style="list-style-type: none"> - chemical resistance - regulatory status 	

The information contained in this document is based on information obtain from raw material suppliers, data selected from the literature and specific testing, but shall in no event be held to constitute or imply any warranty, undertaking, express or implied commitment from our part. Our formal specifications define the limit of our commitment. No liability whatsoever can be accepted by Knudsen Extrusion ApS regarding the handling or use of the product or products concerned which must in all cases be employed in accordance with all relevant laws and/or regulations in force in the country or countries concerned.

